

PHOTO NOT
AVAILABLE

Specification:

Heavy-duty gas range with oven, Model M45R. Two (2) 17" (432mm) front fired spectro-heat hot tops, total 90,000 BTU (26.37 kW). 34" (864mm) wide x 38" (965mm) deep, including 7½" (191mm) deep stainless steel front rail. Porcelain enamel oven interior measuring 26¼" (667mm) wide x 13-½" (343mm) high x 29" (737mm) deep. 40,000 BTU (11.72 kW) cast iron oven burner. Stainless steel front with black powder coat epoxy sides. 130,000 BTU (38.09 kW) total. Natural or propane gas. AGA, CGA certified and NSF listed. MST prefix - models carry CE mark for Europe. (Also available with storage base with doors, Model M45S, and modular top, Model M45T).

Standard Features:

- Stainless steel front; black powder coat epoxy sides
- 6" (152mm) chrome steel adjustable legs
- 7-1/2" (191mm) stainless steel front rail
- Two extra-heavy cast iron top sections
- Removable cast iron ring and lid
- Heavy gauge, aluminized steel radiation baffle system
- 1-piece Stainless Steel drip tray
- Piezo spark ignition for oven
- Fully porcelainized oven interior (M45R)
- 40,000 BTU, (11.72 kW), cast iron oven burner
- Storage base interior of aluminized steel w/shelf (M45S)
- Modular top available (M45T)
- 1-year limited parts & labor warranty (USA & Canada Only)

Optional Features:

- Stainless steel left, right or both sides
- Stainless steel main back
- Stainless steel common front rail up to 68" (1728mm) wide (two or more units in a battery)
- Stainless steel oven interior
- Convection oven base, add C to Model No., e.g., M45RC
- Additional oven racks
- Rear gas connection, 3/4" or 1-1/4" NPT; exterior mount, left or right, (add 4"/102mm) to range width
- End caps and cover, (no charge)-must specify
- 4-Swivel casters w/front brakes
- 4-Polyurethane non-marking swivel casters w/front brakes
- 6" (152mm) stainless steel adjustable legs
- 4" (102mm) chrome steel adjustable legs
- Toe base (not for use with "RC" oven)
- Storage base shelf of stainless steel
- Single deck stainless steel tubular high shelf
- Double deck stainless steel tubular high shelf
- 10" (254mm) high stainless steel backguard
- 17" (432mm) high stainless steel backguard
- 33" (838mm) high stainless steel backguard
- Stainless steel vertical flue riser, 13"W x 33"H, (330mm x 839mm)
- MST model prefix - Sentry total flame failur protection on all burners, e.g. MST45R
- E-model suffix-electric spark ignition on all pilots for MST models only, e.g. MST45RE
- 230 volt, 50 cycle components, RC motor and/or electric ignition (export)
- Celsius dial for oven thermostat (no charge)

NOTE: Ranges supplied with casters must be installed with an approved restraining device.



Garland Commercial Industries, Inc.
 185 East South Street
 Freeland, Pennsylvania 18224
 Phone: (570) 636-1000
 Fax: (570) 636-3903

Garland Commercial Ranges Ltd
 1177 Kamato Road, Mississauga, Ontario
 L4W 1X4 CANADA
 Phone: 905-624-0260
 Fax: 905-624-5669

Enodis UK LTD
 Swallowfield Way, Hayes, Middlesex
 UB3 1DQ ENGLAND
 Telephone: 081-561-0433
 Fax: 081-848-0041



Item #: _____

Models: M45R, M45S, M45T

Product Name: Master Series

Front-Fired Spectro-Heat Hot Top

Product	Width: In(mm)	Depth: In(mm)	Height: In(mm) (w/ NSF Legs)	Height: In(mm) (w/o NSF Legs)	Oven/Storage Base Interior: in(mm)		
					Width	Depth	Height
M45R	34(864)	38(965)	36-3/8(924)	30-3/8(772)	26-1/4(667)	29(737)**	13-1/2(343)
M45S	34(864)	38(965)	36-3/8(924)	36-3/8(924)	26(665)	30-1/2(773)	20-1/2(519)
M45T	34(864)	38(965)	36-3/8(924) w/stand	6-7/8 (175) w/o stand*	N/A	N/A	N/A


*Modular top has 1-1/2" seating flanges. **RC oven is 25"(635mm) deep.

NOTE: MS45T & MST45T are 9-1/2" 241mm high

INPUT-BTU/hr (Natural Gas)	M45R	kW Equivalent	M45S	kW Equivalent	M45T	kW Equivalent
Top Section	90,000	26.37	90,000	26.37	90,000	26.37
Oven	40,000	11.72	N/A	-	N/A	-
TOTAL	130,000	38.37	90,000	26.37	90,000	26.37

RC=Range w/Convection Oven R=Range w/Oven S=Range w/Storage Base T=Modular Top

INSTALLATION NOTES			Shipping Wt: (Lb/Kg)	
Combustible Wall Clearances ¹	Entry Clearances	Manifold Pressure	M45R	510/232
			M45S	410/186
Sides: 14" (356mm) Back: 6" (152mm)	Crated: 39-1/4" (997mm) Uncrated: 34-1/4" (870mm)	Natural: 6" WC (15mbar) Propane: 10" WC (25mbar)	M45T	305/138



¹NOTE: Installation clearance reductions are applicable only where local codes permit.


Data applies only to North America

Gas input ratings shown here are for installations up to 2,000 ft. (610m) above sea level. Specify altitudes over 2,000 ft.

Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard NFPA96. (for North America only)

Electrical characteristics each RC oven: 1/3 HP motor, 120 VAC, single phase, 3.4 amps, 6 ft. (1.8m) power supply cord provided. 230 VAC export is direct connect, single phase, 50 Hz.

Please specify gas type when ordering.



Continuous product improvement is a Garland policy.