

Item #:

Models: S282/S283

Product Name: 60" Starfire Sentry Series Medium Duty Gas Range

Standard Features:

- Flame failure and spark ignition on all concealed
- Extra heavy duty cast iron top and ring rates
- Stainless steel exterior
- 24,000 BTU (Natural Gas) Starfire Burners (6) or 20,000 BTU (Propane Gas) Starfire Burners (6)
- 30,000 BTU/8.79 kW race track even heat oven
- Heavy duty "FDO" oven thermostat (150°-500°F/ 66°-260°C range)
- 17" (432mm) stainless steel backguard with slotted enameled cap
- 24" (610mm) wide raised griddle/broiler (right side only) actual broiler section 19" (463mm) wide
- Standard oven(s); fully porcelain interior which includes oven bottom, top, rear, embossed sides, and inside door liner.
- Removable nickel plated four position oven rack guides
- Nickel plated oven rack (one per standard oven)
- Storage base in lieu of one oven; Model S282
- Stainless steel 6" (152mm) legs with leveling inserts

Optional Features:

- ☐ Convection oven base: for (1) CO base, add suffix RC; for (2) CO bases, add suffix RC2
- ☐ Stainless steel mainback for backguard flue risers and highsleves
- ☐ Stainless steel front and side high shelf
- ☐ Total sentry flame failure protection on all burners, add prefix "T" (i.e. ST283) Only models beginning with prefix "ST" are "CE" approved
- ☐ Electric spark ignition add suffix E (i.e. S283E) requires single phase 115v 60H, 240v, 50 Hz electric connection.
- □ 12" (610mm) hot top section; 3/8" (10mm) thick, (Add suffix - 1, -2 or -3); standard on left or specify location
- ☐ Additional oven rack
- ☐ Casters

NOTE: Ranges supplied with casters must be installed with an approved restraining device.



Model ST283

S282 Single Oven & Storage Base Model & S283 Double Oven Model **Specifications:**

Gas medium duty range with full size porcelain interior oven(s), 60" (1524mm) wide. (6) open top starfire burners with cast iron top and ring grates, 24" (610mm) manual control griddle/ broiler. Stainless steel exterior with stainless steel low profile backguard with slotted enameled cap. S282 has storage base on right. Recommended for churches, schools, cafes, and small restaurants.



http://www.Garland-Group.com

Garland Commercial Industries, Inc.

185 East South Street Freeland, Pennsylvania 18224 Phone: (570) 636-1000 Fax: (570) 636-3903

Garland Commercial Ranges Ltd

1177 Kamato Road, Mississauga, Ontario L4W 1X4 CANADA Phone: 905-624-0260 Fax: 905-624-5669

Enodis UK LTD

Swallowfield Way, Hayes, Middlesex **UB3 1DQ ENGLAND** Telephone: 081-561-0433 Fax: 081-848-0041

Printed in USA



Item #:_____

Models:S282/S283

Product Name: 60" Starfire Sentry Series Medium Duty Gas Range

Input Rating Per Burner (Natural Gas)								Operating Pressure	
Open*		Hot Top**		Griddle/Broiler (3 burners)		Oven		Operating Pressure "WC/ mbar	
BTU	kW	BTU	kW	BTU	kW	BTU	kW	Natural	Propane
24,000	7.03	18,000	5.27	14,500	4.5	30,000	8.78	4.5/11.25	10/25


Gas input ratings shown for installations up to 2000 ft., (610m), above sea level. Please specify altitudes over 2000 ft. Please specify gas type when ordering.

- * Two (2) burners per 12" (610mm) section, (rated at 20,000BTU/5.86kW with Propane)
- ** One (1) burner per optional 12" (610mm) section, (replaces 2 open burners); add suffix: -1, -2 or -3; standard on left

Exterio	r Dimension	s	Oven	Interior Dimer	Installation Clearances		
Height w/shelf	Width	Depth	Height	Width	Depth	Sides	Rear
59-1/2" (1511mm)	60" (1524mm)	33" (838mm)	13-12" (343mm)	26-1/4" (667mm)	22" (559mm)	6" (152mm)	6" (152mm)

NOTE: Not available for dais mounting. Do not install or mount on curb or dais base, insufficient combustion air supply.

This product is not approved for residential use.




	60" [1524mm]						
1							
17" [432mm] _{\rightarrow}							
1	• • • •						
4-11/16 [119mm]	• • • • • • • • • • • • • • • • • • • •						
31-3/4" [806mm]							
L6" MIN [152mm]	S283 Depicted						

	MODEL S283	Ship W		Entry Clearances			
	5203	Lbs.	Kg	Crated	Uncrated		
	STD	885	402	46" (1168mm)	34 (864mm)		
	RC	935	424	46" (1168mm)	39 (991mm)		
1 ess 75 Lb/35 Kg for Model S282 STD and BC							

1Less 75 Lb/35 Kg for Model S282 STD and RC

Installation notes: For RC oven add 5" (127mm) to overall depth. Electric characteristics each RC oven: 1/3 HP motor; 120VAC, Single phase, 3.4 Amps (RC2 Model - 6.8 Amps), (6 Ft/1829mm power supply cord provided).

NOTE: Installation clearance reductions are applicable only where local codes permit



Continuous product improvement is a Garland policy. Specifications and design are subject to change without notice.

Form #S283 (05/05)