



Model S284

Specification:

Gas medium duty range with two full-size ovens, 60" (1524mm) wide, (10) open top burners with extra heavy duty cast iron tops and ring grates. Stainless steel 10" (254mm) high backguard with slotted black enameled cap. Available with optional hot top(s) and/or griddle. Available with convection base oven(s).



NOTE: CE certification applies only to models with prefix "T" -see Optional Features

Standard Features:

- Flame failure and spark ignition on all concealed burners
- Extra heavy duty cast iron tops and ring grates
- Stainless steel exterior
- 24,000 BTU/7.03 kW (natural gas) Starfire burners (10) or 20,000 BTU/5.86 kW (propane gas) Starfire burners
- 30,000 BTU/8.79 kW race track even heat oven burner
- Heavy duty "FDO" oven thermostat accurate to $\pm 10^{\circ}\text{F}$ ($\pm 5^{\circ}\text{C}$) temperature range 150°-500° (66°C-260°C)
- Two standard ovens; fully porcelain interior which includes oven bottom, top, rear, embossed sides, and inside door liner.
- Removable nickel plated four position oven rack guides
- Nickel plated oven rack, (one per oven)
- 10" (254mm) high stainless steel back guard with slotted black enameled angled cap
- 6" (152mm) high stainless steel legs - adjustable
- Gas Regulator
- No visible screw fixings
- One year limited warranty on parts & labor (USA & Canada only)

Optional Features:

- ☐ Convection oven base: for (1) CO base, add suffix RC; for (2) CO bases, add suffix RC2
- ☐ Heavy duty 5/8" (16mm) griddle plates available in the following widths - 12" (305mm), 24" (610mm), 36" (914mm) & 48" (1219mm) standard on RHS, optional on LHS
- ☐ Hot tops 3/8" (10mm) thick - standard on LHS, optional on RHS
- ☐ Sentry safety protection to open burners (add prefix T, i.e. ST284)
- ☐ Electric spark ignition (add suffix E, i.e. S284E) requires single phase 115v, 60H, 240v, 50Hz electrical connection
- ☐ Additional oven rack
- ☐ Stainless steel back-guard and plate shelf 17" (432mm) high stainless steel backguard
- ☐ Stainless steel main back
- ☐ 6" (152mm) stainless steel legs
- ☐ Casters

NOTE: Ranges supplied with casters must be installed with an approved restraining device.

