

# The "Mini's" among professionals in gas or electric

Gas and electric RATIONAL SelfCooking Centers® have absolutely identical dimensions, features and performance.

Special versions are available for ships and prisons, and there is a SelfCooking Center® with integral fat drainage. Please use the reply card on the last page to send for our special brochure.

## Model SCC 61

**Electric and gas**  
Capacity: 6 x 1/1 GN  
Number of meals per day: 30-80  
Lengthwise loading for 1/1, 1/2, 2/3, 1/3, 2/8 GN  
Width: 847 mm (33 1/4")  
Depth: 771 mm (30 3/8")  
Height: 757 mm (29 3/4")  
Water supply: R 3/4"  
Water drain: DN 50  
Water pressure: 150-600 hPa or 0.15-0.6 Mpa

**Electric**  
Weight: 110 kg  
Connected load: 10 kW  
Fuse protection: 3 x 16 A  
Mains connection: 3 NAC 400 V  
"Dry heat" connection: 9 kW  
"Moist heat" connection: 9 kW  
Cable cross-section: 5 x 2.5 mm<sup>2</sup>

**Gas**  
Weight: 126 kg  
Height incl. gas draft diverter: 996 mm  
Electricity connection: 0.3 kW  
Fuse protection: 1 x 16 A  
Mains connection: 1 NAC 230 V  
Gas supply/connection: R 3/4"  
Cable cross-section: 3 x 2.5 mm<sup>2</sup>

**Natural gas/LPG liquid gas**  
Max. rated thermal load: 11 kW/12kW  
"Dry heat" connection: 11 kW/12 kW  
"Moist heat" connection: 11 kW/12kW

## Model SCC 62

**Electric and gas**  
Capacity: 6 x 2/1 GN  
Number of meals per day: 60-160  
Lengthwise loading for 2/1, 1/1 GN  
Width: 1,069 mm (42")  
Depth: 971 mm (30 3/8")  
Height: 757 mm (29 3/4")  
Water supply: R 3/4"  
Water drain: DN 50  
Water pressure: 150-600 hPa or 0.15-0.6 Mpa

**Electric**  
Weight: 142.5 kg  
Connected load: 21 kW  
Fuse protection: 3 x 32 A  
Mains connection: 3 NAC 400 V  
"Dry heat" connection: 20 kW  
"Moist heat" connection: 18 kW  
Cable cross-section: 5 x 4 mm<sup>2</sup>

**Gas**  
Weight: 168 kg  
Height incl. gas draft diverter: 996 mm  
Electricity connection: 0.35 kW  
Fuse protection: 1 x 16 A  
Mains connection: 1 NAC 230 V  
Gas supply/connection: R 3/4"  
Cable cross-section: 3 x 2.5 mm<sup>2</sup>

**Natural gas/LPG liquid gas**  
Max. rated thermal load: 21.5 kW/23 kW  
"Dry heat" connection: 21.5 kW/23 kW  
"Moist heat" connection: 20 kW/21 kW


## Model SCC 101

**Electric and Gas**  
Capacity: 10 x 1/1 GN  
Number of meals per day: 80-150  
Lengthwise loading for 1/1, 1/2, 2/3, 1/3, 2/8 GN  
Width: 847 mm (33 1/4")  
Depth: 771 mm (30 3/8")  
Height: 1,017 mm (44")  
Water supply: R 3/4"  
Water drain: DN 50  
Water pressure: 150-600 hPa or 0.15-0.6 Mpa

**Electric**  
Weight: 135.5 kg  
Connected load: 19 kW  
Fuse protection: 3 x 32 A  
Mains connection: 3 NAC 400 V  
"Dry heat" connection: 18 kW  
"Moist heat" connection: 18 kW  
Cable cross-section: 5 x 4 mm<sup>2</sup>

**Gas**  
Weight: 154.5 kg  
Height incl. gas draft diverter: 1,256 mm  
Electricity connection: 0.35 kW  
Fuse protection: 1 x 16 A  
Mains connection: 1 NAC 230 V  
Gas supply/connection: R 3/4"  
Cable cross-section: 3 x 2.5 mm<sup>2</sup>

**Natural gas/LPG liquid gas**  
Max. rated thermal load: 21.5 kW/23 kW  
"Dry heat" connection: 21.5 kW/23 kW  
"Moist heat" connection: 20 kW/21 kW



NRTL/C

## Model SCC 102

### Electric and gas

Capacity: 10 x 2/1 GN  
Number of meals per day: 150-300  
Lengthwise loading for 2/1, 1/1 GN  
Width: 1,069 mm (42")  
Depth: 971 mm (38 1/4")  
Height: 1,017 mm (40")  
Water supply: R 3/4"  
Water drain: DN 50  
Water pressure: 150-600 hPa or 0.15-0.6 Mpa

### Electric

Weight: 182 kg  
Connected load: 37 kW  
Fuse protection: 3 x 63 A  
Mains connection: 3 NAC 400 V  
"Dry heat" connection: 36 kW  
"Moist heat" connection: 36 kW  
Cable cross-section: 5 x 10 mm<sup>2</sup>

### Gas

Weight: 198 kg  
Height incl. gas draft diverter: 1,256 mm  
Electricity connection: 0.45 kW  
Fuse protection: 1 x 16 A  
Mains connection: 1 NAC 230 V  
Gas supply/connection: R 3/4"  
Cable cross-section: 3 x 2.5 mm<sup>2</sup>

### Natural gas/LPG liquid gas

Max. rated thermal load: 32 kW/34 kW  
"Dry heat" connection: 32 kW/34 kW  
"Moist heat" connection: 32 kW/34 kW

## Model SCC 201

### Electric and gas

Capacity: 20 x 1/1 GN  
Number of meals per day: 150-300  
Lengthwise loading for 1/1, 1/2, 2/3, 1/3, 2/8 GN  
Width: 879 mm (34 1/2")  
Depth: 791 mm (31 1/8")  
Height: 1,782 mm (70 1/8")  
Water supply: R 3/4"  
Water drain: DN 50  
Water pressure: 150-600 hPa or 0.15-0.6 Mpa

### Electric

Weight: 258 kg  
Connected load: 37 kW  
Fuse protection: 3 x 63 A  
Mains connection: 3 NAC 400 V  
"Dry heat" connection: 36 kW  
"Moist heat" connection: 36 kW  
Cable cross-section: 5 x 10 mm<sup>2</sup>

### Gas

Weight: 286 kg  
Height incl. gas draft diverter: 2,021 mm  
Electricity connection: 0.8 kW  
Fuse protection: 1 x 16 A  
Mains connection: 1 NAC 230 V  
Gas supply/connection: R 3/4"  
Cable cross-section: 3 x 2.5 mm<sup>2</sup>

### Natural gas/LPG liquid gas

Max. rated thermal load: 43 kW/46 kW  
"Dry heat" connection: 43 kW/46 kW  
"Moist heat" connection: 32 kW/33.5 kW

## Model SCC 202

### Electric and Gas

Capacity: 20 x 2/1 GN  
Number of meals per day: 300-500  
Lengthwise loading for 2/1, 1/1 GN  
Width: 1,084 mm (42 1/2")  
Depth: 996 mm (39 2/8")  
Height: 1,782 mm (70 1/8")  
Water supply: R 3/4"  
Water drain: DN 50  
Water pressure: 150-600 hPa or 0.15-0.6 Mpa

### Electric

Weight: 332 kg  
Connected load: 62 kW  
Fuse protection: 3 x 100 A  
Mains connection: 3 NAC 400 V  
"Dry heat" connection: 60 kW  
"Moist heat" connection: 54 kW  
Cable cross-section: 5 x 25 mm<sup>2</sup>

### Gas

Weight: 370.5 kg  
Height incl. gas draft diverter: 2,021 mm  
Electricity connection: 1.0 kW  
Fuse protection: 1 x 16 A  
Mains connection: 1 NAC 230 V  
Gas supply/connection: R 3/4"  
Cable cross-section: 3 x 2.5 mm<sup>2</sup>

### Natural gas/LPG liquid gas

Max. rated thermal load: 64 kW/67 kW  
"Dry heat" connection: 64 kW/67 kW  
"Moist heat" connection: 51 kW/53 kW

